

DERBIFLASH RS FLEECE

DESCRIPTION

Derbiflash RS Fleece is a nonwoven, polyester reinforcement designed for use with Derbiflash RS liquid-applied systems. Besides improving membrane strength and durability, polyester reinforcement provides additional puncture resistance, and crack bridging capabilities.

ADVANTAGES

- ▶ Adds membrane strength and puncture resistance
- ▶ Saturates quickly to provide strong bond between layers
- ▶ Soft grade fabric easily conforms to irregular shapes and surfaces for ease of application
- ▶ Helps maintain membrane uniformity

STORAGE

When not in use, store fleece in a sealed wrap or container to protect from contaminants. Fleece is specifically designed to absorb liquid membrane components. Exposure to moisture (rain, condensation, high humidity, etc.) dust, dirt and debris will compromise and may cause failure of the finished application. Contaminated fleece MUST be disposed of and replaced.

FLEECE DIMENSIONS & COVERAGE

ROLL WIDTH	ROLL LENGTH	NET COVERAGE
4 in	164 ft	53 ft ²
10 in	164 ft	134 ft ²
13.8 in	164 ft	188 ft ²
20.7 in	164 ft	285 ft ²
41.3 in	164 ft	565 ft ²



TYPICAL PROPERTIES

PROPERTY	VALUE
Material	Polyester
Color	White
Thickness	25 mil

PROPERTY	MD	CD
Tensile Strength	53 lbf	59 lbf
Elongation	70 %	80 %

** All values shown are nominal and subject to normal manufacturing tolerances*

Refer to the Derbiflash RS Application Guide for complete application specifications and guidelines.