

PRS GLASS PLY IV

Fiberglass ply sheet

ADVANTAGES

- ▶ High performance fiberglass ply sheet with excellent tensile strength
- ▶ Meets or exceeds ASTM D2178 Type IV specifications
- ▶ Product carries an Underwriters Laboratories G1 classification
- ▶ Made from inorganic material that resists rotting
- ▶ Porosity of the felt allows for better asphalt penetration
- ▶ Can be applied using hot asphalt, PERMASTIC cold adhesive or mechanical fasteners

TECHNICAL CHARACTERISTICS

PRS Glass Ply IV Results*

PROPERTY	MD	XMD	ASTM
Peak Load @ 73.4°F; lbf/in	44	44	D2178

* All values shown are nominal and subject to normal manufacturing tolerances.

PRODUCT INFORMATION*

PROPERTY	VALUE
Length; ft (m)	180 (54.9)
Width; in (m)	36 (0.9)
Weight; lb (kg)	45 (20.4)
Net Coverage; ft ² (m ²)**	487 (45.2)

* All values shown are nominal and subject to normal manufacturing tolerances

**Net coverage is configured to reflect overlaps according to Performance Roof Systems specifications.
Coverage rates can vary depending on project specifications.

PACKAGING & STORAGE

Packaged 20 rolls per pallet. Rolls should be stored on end, on raised platforms protected from the weather.

