

PERFLASH

Modified bitumen flashing cement

ADVANTAGES

- ▶ Premium grade modified asphalt flashing formulated for adhering APP modified bitumen flashing membranes to vertical surfaces
- ▶ Excellent adhesion and enhanced waterproofing due to over 85% solids content.
- ▶ Product can also be used for filling pitch pans, setting roof drain leads and metal flashing components.
- ▶ VOC compliant —meets stringent EPA air quality standards with low fumes
- ▶ No kettles, dangerous chemicals
- ▶ Meets the requirements of ASTM 4586 Type II

PRODUCT INFORMATION*

PROPERTY	VALUE
Weight; lb/gal (kg/L)	9.1 (1.09)
VOC; lb/gal (g/L)	1.3 (165)
Flash point; °F (°C)	> 120 (>48.8)
Non-volatile contents	86% solids
Solids Volume; %	> 50

* All values shown are nominal and subject to normal manufacturing tolerances.

APPLICATION

RATE: 7.5 gallons per 100 sq ft (31 sq m) at 1/8 inch
 Note: Coverage may vary with absorption

TOOLS: A trowel or a gloved hand to distribute evenly

PACKAGING & STORAGE

PERFLASH is available in the following containers sizes:

- 30 ounce cartridge (0.88 L)
- 5 gallon pail (18.9 L)

Approximate shelf life is 12 months with proper storage.

