

# PERMASTIC

Asphaltic-based cold-applied adhesive for modified bitumen membranes

## ADVANTAGES

- ▶ Cold applied adhesive for use with modified bitumen membranes, base sheets, and other cold process roofing systems.
- ▶ Excellent adhesion and enhanced waterproofing due to over 80% solids content.
- ▶ Thixotropic properties from additives improve stability.
- ▶ Improved productivity which minimizes open roofs.
- ▶ Available in environmentally friendly reusable pails, drums and tanks
- ▶ No kettles, dangerous chemicals and low VOC emissions provides a safer work environment.
- ▶ Meets the requirements of ASTM D3019, Type III, Grade 2



## PRODUCT INFORMATION\*

PROPERTY	VALUE
<b>Weight;</b> lb/gal (kg/L)	<b>9.0</b> (1.07)
<b>VOC;</b> lb/gal (g/L)	<b>1.6</b> (200)
<b>Flash point;</b> °F (°C)	<b>&gt; 105</b> (>40.5)
<b>Non-volatile contents</b>	<b>78 - 83% solids</b>

\* All values shown are nominal and subject to normal manufacturing tolerances.

## APPLICATION

**RATE:** 2.0 gallons per 100 sq ft (90.81 sq m)

**TOOLS:** A notched squeegee or spray apparatus to distribute cold process adhesives.  
A 20 lb steel roller to roll all side and ends laps that will be heat welded.

## PACKAGING & STORAGE

PERMASTIC is available in the following containers sizes:

- 5 gallon pail (18.9 L) (4.7 gal per volume)
- 55 gallon drum (208.2 L) (53.3 gal per volume)
- 350 gallon reusable tank (1,323 L)

Store in a well-ventilated area far away from any heat source.